

Version 4.0

Revision Date 01/20/2016 Ref. 150000004382

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

#### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Staurolite Products – Ultra and Coarse

Product Grade/Type : Starblast<sup>™</sup> Ultra Blasting Abrasive, Coarse Staurolite

Product Use : Abrasive blasting, Sand blasting, For industrial use only.

Restrictions on use : Do not use product for anything outside of the above specified uses

Manufacturer/Supplier : The Chemours Company FC, LLC

1007 Market Street Wilmington, DE 19899 United States of America

Product Information : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Medical Emergency : 1-866-595-1473 (outside the U.S. 1-302-773-2000)

Transport Emergency : CHEMTREC: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Other information : professional use

### **SECTION 2. HAZARDS IDENTIFICATION**

Product hazard category

Carcinogenicity Category 1A Specific target organ toxicity - Category 2

repeated exposure



Version 4.0

Revision Date 01/20/2016 Ref. 150000004382

**Label content** 

Pictogram :



Signal word : Danger

Hazardous warnings : May cause cancer.

May cause damage to organs through prolonged or repeated exposure.

(Lungs)

Hazardous prevention

measures

: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

IF exposed or concerned: Get medical advice/ attention.

Store locked up.

Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

The product, as shipped, poses a minimal inhalation health hazard because the bulk of the particles are in the non-inhalable size range. However, if during handling or use the particles are broken down to a size that can be inhaled, the dusts may be harmful to the respiratory system., Product dust may be irritating to eyes, skin and respiratory system., Use appropriate Personal Protective Equipment (PPE) such as an air supplied respirator approved for sandblasting., Wash hands before breaks and at the end of workday.

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 100 %

# Safety Data Sheet



# Staurolite Products - Ultra and Coarse

Version 4.0

Revision Date 01/20/2016 Ref. 150000004382

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Staurolite	12182-56-8	83 - 88 %
Iron titanium trioxide	12022-71-8	<=10 %
Quartz	14808-60-7	<=7 %
Rutile (TiO2)	1317-80-2	<=5 %
Zircon	14940-68-2	<=4 %
Kyanite	1302-76-7	<=3 %

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

### **SECTION 4. FIRST AID MEASURES**

General advice : Call a physician if symptoms occur.

Inhalation : Remove person to fresh air. If signs/symptoms continue, get medical attention.



Version 4.0

Revision Date 01/20/2016 Ref. 150000004382

Skin contact : Wash off with soap and water.

Eye contact : Rinse with plenty of water.

Ingestion : No specific intervention is indicated. Consult a physician if necessary.

Most important

symptoms/effects, acute

and delayed

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : No special protective equipment required.

: irritant effects

### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and

the surrounding environment.

Unsuitable extinguishing

media

: None known.

Specific hazards : Not a fire or explosion hazard.

Special protective equipment

for firefighters

: No special protective equipment required.

Further information : The product itself does not burn.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Safeguards (Personnel) : Avoid breathing dust.



Version 4.0

Revision Date 01/20/2016 Ref. 150000004382

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Spill Cleanup : Pick up and arrange disposal without creating dust. After cleaning, flush away

traces with water.

Accidental Release Measures : For disposal considerations see section 13.

### **SECTION 7. HANDLING AND STORAGE**

Handling (Personnel) : Avoid formation of additional inhalable particles. If handling inhalable

particulates, use of gloves and washing before eating, drinking, applying cosmetics or smoking is advisable to minimize dust inhalation or ingestion of

residue from hands.

Avoid breathing dust. Wash hands before breaks and at the end of workday.

Handling (Physical Aspects) : This is a fully oxidized mineral product. As such it cannot support combustion

or participate in a dust explosion.

Dust explosion class : Not applicable

Storage : No special storage conditions required.

Storage period : No applicable data available.

Storage temperature : No applicable data available.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls : Use sufficient ventilation to keep employee exposure below recommended

limits. If using this product as an abrasive blast agent in confined areas, airborne dust levels should be controlled by physical enclosure of the abrasive blasting operation. The enclosure should be exhaust ventilated in

accordance with 29 CFR 1910.94 Ventilation (a) Abrasive blasting.

Personal protective equipment

Respiratory protection : For abrasive blasting use a type CE abrasive-blast supplied-air respirator



Version 4.0

Revision Date 01/20/2016

Ref. 150000004382

covering head, neck, and shoulders to provide protection from rebound abrasive per 29 CFR 1910.94 (a)(5).

A certified air-purifying respirator with a type 100 (high efficiency) particulate cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Use a certified positive pressure air-supplied respirator in circumstances where air-purifying respirators may not provide adequate protection. Provide adequate ventilation. Evaluations as to which personnel may require respiratory protection should include consideration of potential exposure to bystanders near dust generating activities such as, for example, abrasive blasting.

Eye protection : Wear safety glasses with side shields.

Skin and body protection : Where there is potential for skin contact have available and wear as

appropriate impervious gloves, apron, pants, and jacket.

Protective measures : The stated hazards of this material are based on non-inhalable particles that

are the bulk fraction of the delivered product. However, if during handling or use the particles are broken down to the inhalable or respirable size range, the dusts may be harmful to the respiratory system. Inhalable quartz is an IARC Category 1 carcinogen and applicable exposure limits should be

referenced.

Exposure Guidelines
Exposure Limit Values

Quartz

Permissible (OSHA) 2.4 millions of particles per cubic foot of air TWA

exposure limit: Respirable.

Remarks The exposure limit is calculated from the

equation, 250/(%SiO2+5), using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits.

TMA Despirable

Permissible (OSHA) 0.1 mg/m3 TWA Respirable. exposure limit:

Remarks The exposure limit is calculated from the

equation, 10/(%SiO2+2), using a value of



Version 4.0

Revision Date 01/20/2016 Ref. 150000004382

100% SiO2. Lower percentages of SiO2

will yield higher exposure limits.

Permissible (OSHA) 0.3 mg/m3 TWA Total dust.

exposure limit:

Remarks The exposure limit is calculated from the

equation, 30/(%SiO2+2), using a value of 100% SiO2. Lower values of % SiO2 will

give higher exposure limits.

TLV (ACGIH) 0.025 mg/m3 TWA Respirable fraction.

Rutile (TiO2)

Permissible (OSHA) 15 mg/m3 AEL \* Total dust.

exposure limit:

TLV (ACGIH) 10 mg/m3 AEL \* Total dust.

Zircon

Permissible (OSHA) 5 mg/m3 8 hr. TWA as Zr

exposure limit:

TLV (ACGIH) 5 mg/m3 TWA as Zr TLV (ACGIH) 10 mg/m3 STEL as Zr

Kyanite

TLV (ACGIH) 1 mg/m3 TWA Respirable fraction.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance

Physical state : solid

Form : Solid form, crystalline

Color : red brown

Odor : odourless

# Safety Data Sheet



## Staurolite Products - Ultra and Coarse

Version 4.0

Revision Date 01/20/2016 Ref. 150000004382

Odor threshold : Not applicable

pH : Not applicable

Melting point/freezing point : 1,370 °C (2,498 °F)

Boiling point/boiling range : Not applicable

Flash point : does not flash

Evaporation rate : Not applicable

Flammability (solid, gas) : The product is not flammable.

Upper explosion limit : Not applicable

Lower explosion limit : Not applicable

Vapor pressure : Not applicable

Vapor density : Not applicable

Specific gravity (Relative

density)

: 3.7

Water solubility : insoluble

Solubility(ies) : Not applicable

Partition coefficient: n-

octanol/water

: Not applicable

Auto-ignition temperature : Not applicable

Decomposition temperature : Not applicable

Viscosity, kinematic : Not applicable

Viscosity, dynamic : Not applicable



Version 4.0

Revision Date 01/20/2016 Ref. 150000004382

### SECTION 10. STABILITY AND REACTIVITY

Reactivity None reasonably foreseeable.

Chemical stability Stable

Possibility of hazardous

reactions

None known.

Conditions to avoid Not applicable

Incompatible materials None known.

Hazardous decomposition

products

Not applicable

### SECTION 11. TOXICOLOGICAL INFORMATION

Staurolite Products - Ultra and Coarse Inhalation

The objective of the study was to compare the lung toxicity of a set of abrasive substitutes for silica dust (garnet, staurolite, coal slag, specular hematite, and treated sand) to that of blasting sand. Rats were intratracheally instilled with 2.5 or 10 mg/kg of the various test substances and pulmonary toxicity endpoints were measured at 4 weeks postexposure. The biomarkers included lung inflammation and cytotoxicity endpoints. In addition, the investigators measured alveolar macrophage activation. The results indicated that blasting sand produced evidence of pulmonary toxicity/inflammation and lung fibrosis. Garnet, staurolite, and treated sand exposures induced pulmonary hazard effects and inflammation that were viewed as similar to blasting sand, while coal slag instillation produced greater pulmonary damage and inflammation than blasting sand. In contrast, specular hematite did not significantly increased levels of inflammation and cytotoxicity and did not stimulate macrophage activation. [Hubbs AF et al., Toxicological Sciences volume 61: 135-143, 2001] The results of this study should be viewed as a preliminary, screeningtype pulmonary toxicity study which utilized very high, overload doses.

Subsequently, the NIOSH researchers followed up on the Hubbs et al., study with another lung toxicity screening study of blasting agents



Version 4.0

Revision Date 01/20/2016 Ref. 150000004382

["Comparative pulmonary toxicity of blasting sand and five substitute abrasive blasting agents" – DW Porter et al., J Toxicol Environ Health A 65:1121-40, 2002]. The additional test substances included steel grit, copper slag, nickel slag, crushed glass and olivine. The authors reported that steel grit produced less lung toxicity than blasting sand

or any of the other abrasive blasting substitutes

Iron titanium trioxide

Skin irritation : No skin irritation, animals (unspecified species)

Eye irritation : No eye irritation, animals (unspecified species)

Skin sensitization : Does not cause skin sensitisation., animals (unspecified species)

Quartz

Oral LD50 : > 11,000 mg/kg, Rat

Bloody nasal discharge

Weight loss

Skin irritation : No skin irritation, Rabbit

Eye irritation : No eye irritation, Rabbit

Skin sensitization : Does not cause skin sensitisation., Guinea pig

Repeated dose toxicity : Inhalation

Rat

-

Target Organs: Lungs

The substance or mixture is classified as specific target organ

toxicant, repeated exposure, Category 2.

Fluid retention in lungs (pulmonary oedema), lung effects,

Inflammation, Chronic lung disease, Fibrosis

Carcinogenicity : Human carcinogen.

An increased incidence of tumours was observed in laboratory

animals.

An increased risk of cancer in humans has been shown in workplace-

based studies.



Version 4.0

Revision Date 01/20/2016 Ref. 150000004382

Rutile (TiO2)

Oral LD50 : > 5,000 mg/kg, Rat

Skin irritation : No skin irritation, Rabbit

Eye irritation : No eye irritation, Rabbit

Skin sensitization : Did not cause sensitisation on laboratory animals., Mouse

Did not cause sensitisation on laboratory animals., Guinea pig

Repeated dose toxicity : Oral

Rat

----

No toxicologically significant effects were found.

Inhalation

Rat

-

No toxicologically significant effects were found.

Carcinogenicity : Not classifiable as a human carcinogen.

In lifetime inhalation studies rats were exposed for 2 years to respectively 10, 50 and 250 mg/m3 of respirable TiO2. Slight lung fibrosis was observed at 50 and 250 mg/m3 levels. Microscopic lung tumours were also observed in 13 percent of the rats exposed to 250

mg/m3, an exposure level that caused lung overloading and

impairment of rat lungs clearance mechanisms.

In further studies, these tumours were found to occur only under particle overload conditions in a uniquely sensitive species, the rat,

and have little or no relevance for humans. The pulmonary

inflammatory response to TiO2 particles exposure was also found to

be much more severe in rats than in other rodent species.

The conclusions of several epidemiology studies on more than 20000 TiO2 industry workers in Europe and the USA did not suggest a carcinogenic effect of TiO2 dust on the human lung. Mortality from other chronic diseases, including other respiratory diseases, was also

not associated with exposure to TiO2 dust.

Based upon all available study results, Chemours scientists conclude



Version 4.0

Revision Date 01/20/2016 Ref. 150000004382

that titanium dioxide will not cause lung cancer or chronic respiratory diseases in humans at concentrations experienced in the workplace.

Mutagenicity : Tests on bacterial or mammalian cell cultures did not show mutagenic

effects.

Animal testing did not show any mutagenic effects.

Reproductive toxicity : Animal testing showed no reproductive toxicity.

Teratogenicity : Animal testing showed no developmental toxicity.

Further information : The toxicological data has been taken from products of similar

composition.

#### Carcinogenicity

The carcinogenicity classifications for this product and/or its ingredients have been determined according to HazCom 2012, Appendix A.6. The classifications may differ from those listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or those found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition).

Material IARC NTP OSHA

Quartz 1 X

Rutile (TiO2) 2B

### SECTION 12. ECOLOGICAL INFORMATION

Aquatic Toxicity Rutile (TiO2)

96 h LC50 : Pimephales promelas (fathead minnow) > 1,000 mg/l

72 h EC50 : Pseudokirchneriella subcapitata (green algae) > 100 mg/l

48 h EC50 : Daphnia magna (Water flea) > 1,000 mg/l



Version 4.0

Revision Date 01/20/2016 Ref. 150000004382

Additional ecological information : Not applicable

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

Waste disposal methods -

Product

: Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of in accordance with local regulations.

#### SECTION 14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

### SECTION 15. REGULATORY INFORMATION

TSCA : On the inventory, or in compliance with the inventory

Other regulations : These products are exempt from Nuclear Regulatory Commission (NRC)

regulations for source material per 10 CFR 40, since it falls under the definition of "unimportant quantity source material" containing less than 0.05% uranium or thorium. Some states may apply NRC type radiation protection standards for NORM above background levels, or may have NORM specific regulations that are determined based upon the radium content. It is recommended that you consult with current regulations.

SARA 313 Regulated

Chemical(s)

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established

by SARA Title III, Section 313.

PA Right to Know Regulated Chemical(s) : Substances on the Pennsylvania Hazardous Substances List present at a concentration of 1% or more (0.01% for Special Hazardous Substances):



Version 4.0

Revision Date 01/20/2016 Ref. 150000004382

Quartz, Rutile (TiO2)

NJ Right to Know Regulated Chemical(s) : Substances on the New Jersey Workplace Hazardous Substance List present at a concentration of 1% or more (0.1% for substances identified as

carcinogens, mutagens or teratogens): Quartz, Rutile (TiO2)

California Prop. 65 : WARNING! This product contains a chemical or chemicals known to the State

of California to cause cancer. Quartz, Rutile (TiO2), Radionuclides

#### **SECTION 16. OTHER INFORMATION**

Restrictions for use : Do not use or resell Chemours<sup>™</sup> materials in medical applications involving

implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such

use. For further information, please contact your Chemours

representative.

These products may not be directly added to food or pharmaceuticals and

are not recommended for use in medical devices or cosmetics.

Starblast<sup>™</sup> is a trademark of The Chemours Company TT, LLC.

Staurolite Products contain trace quantities of naturally occurring radioactive uranium and thorium (less than or equal to 25 ppm uranium plus 175 ppm thorium = 200 ppm total U + Th or 0.02 % w/w, equivalent to 28 pCi/g or less), and radium (less than or equal to 28 pCi/g). Naturally Occurring Radioactive Material, namely uranium, thorium, and their decay products, including radium, is commonly referred to as "NORM".

The main radiological hazard from the product is internal exposure from small amounts of alpha particles given off by inhaled dust. Industrial hygiene practices aimed at control of airborne dust can lessen the potential for exposure. Overexposure by inhalation to inhaled dusts containing radioactive uranium, thorium, and radium may cause lung cancer. Low level gamma radiation in proximity to bulk or bagged stockpiles of these products may present a lesser, external exposure that can be managed by limiting close proximity for long time periods to large volumes of material.

With respect to dust exposure, evaluation and calculation based upon dosimetry (ICRP 68) yield the following guidance to ensure that inhalation intake is less than a 100 mrem/yr public dose reference point for radionuclides.

For a total dust with aerodynamic diameter of 1 um, the calculated reference dust level is 6.9 mg/m3. For a total dust with aerodynamic diameter of 5 um, the calculated reference dust level is 10.8 mg/m3. For a total dust with aerodynamic



Version 4.0

Revision Date 01/20/2016

Ref. 150000004382

diameter of 10 um, the calculated reference dust level is 15.9 mg/m3.

The calculations noted above are based upon 8 hr/day TWAs. It should be noted that for these products, the actual particle physical diameter is approximately 1/2 the effective aerodynamic diameter. For these products, as shipped, with essentially no particles as small as calculated above, the highest total dust level can provide a conservative limit. However, if during handling or use the particles are broken down to finer particle sizes, lower levels of total dust would apply.

These reference calculations for radionuclides may or may not provide the most conservative recommendation vs. other trace contaminants as compared to specific country dust contaminant limit calculations. It is recommended that the user compare and calculate or measure for specific contaminants vs. reference limits, especially if particles are broken down, to determine the most appropriate standard for protection.

Please see www.Chemours.com/Titanium\_Technologies/en\_US/ for the latest version of this MSDS.

Revision Date : 01/20/2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.